

- Cutters & Pliers
- Wire strippers
- Crimpers
- Tweezers
- Screwdrivers & Wrenches
- Metal working
- Parts boxes
- Tool cases
- Tool kits

F-155 WRIST STRAP



● Stainless wrist strap. (SUS304)
Outer plastic coating prevents electrostatic discharges from devices.

- Effective cord length: 1.6 m
- With 1 MΩ resistor
- Alligator clip
- Weight: 65 g
- ESD standard: Ground resistance $7.5 \times 10^5 \leq R_g < 3.5 \times 10^7 \Omega$
* Being worn.



- Soldering irons & Solder
- Parts & Solder removal equipment
- Measuring instruments
- Optical equipment
- Antistatic products
- Clean products
- Chemical products
- Maintenance & Safety products

F-152 WRIST STRAP



Relief from metal allergy
All body contact areas use materials other than metal.

- Effective cord length: 1.6 m
- With 1 MΩ resistor
- Alligator clip
- Weight: 40 g
- ESD standard: Ground resistance $7.5 \times 10^5 \leq R_g < 3.5 \times 10^7 \Omega$ * Being worn.



■ Replacement part
F-152-2 WRIST STRAP
■ For F-152



- Rubber mats
- ESD racks
- ESD trays
- ESD foams & Bags
- Parts boxes
- Parts cabinets
- Wrist straps
- Ionizers
- ESD checkers
- ESD brush

F-153 WRIST STRAP



- Effective cord length: 1.6 m
- With 1 MΩ resistor
- Alligator clip
- Weight: 40 g
- ESD standard: Ground resistance $7.5 \times 10^5 \leq R_g < 3.5 \times 10^7 \Omega$ * Being worn.



■ Replacement part
F-153-2 WRIST STRAP
■ For F-153

